# AX2200e

# WIRELESS

# Point-of-Sale

# **Endless Possibilities**

The ExaDigm NX2200e wireless payment solution brings in the latest innovations in POS functionality over the largest wireless networks for fast-secure transactions, allowing for the utmost mobility while continuing to be fully compliant with payment industry standards.

- **SECURE**Supports the latest industry standards
- SCALABLE EMV & NFC support, including an optional camera
- MOBILE
   Cellular & WiFi support; compact with a long operating battery life



### **CERTIFICATIONS**









# NX2200e



# Features & Benefits

**Security** - Built-in security transaction engine for the highest level of secure payment processing.

**NFC Support** - Improves customer experience by offering support for mobile wallet applications. Certified for both PayPass and PayWave.

**EMV Support** - ExaDigm has embraced future-proof strategies, such as EMV, to give you confidence and trust with every transaction.

**Performance & Design** - ExaDigm's multi-application platform allows for easy integration with other value-added applications, all in one device.

### **Accessories**

**Car Adapter** - Charge your device from the accessory power outlet in your car with this universal car adapter.

**Holster** - The holster safeguards the NX2200e from the elements and is equipped with a belt clip and adjustable shoulder strap to secure the terminal comfortably on the user.

**Li-Ion Battery** - The removable battery provides long operating use without having to be recharged often.

**Multi-Charger** - ExaDigm's multi-charger comes with four battery charging bays, ensuring there is always a charged battery available.

# Terminal Access Portal (TAP)

ExaDigm's Terminal Access Portal (TAP) provides the fastest, most secure and truly cost-effective remote device management tool for a wide range of users. Featuring a user-friendly interface, TAP can be accessed anytime, anywhere, ensuring real-time device management.

# **Specifications**

**Processor** ARM9, 32-bit secure processor

Memory 64 MB Flash, 128 MB SDRAM

**Slots** 4 PSAM card slots

1 SIM card slot 1 SIM/SD card slot

Card Readers Contactless - ISO/IEC 14443

Magstripe - 3 track, bi-directional

Smart card - ISO 7816

**Display** 3.2 inch color capacitive screen, 320 x 240

**Keypad** 10 operational keys, 2 functional keys

Audio 0.8W, mono

**Thermal Printer** Paper roll W x D =  $58 \text{mm} \times 40 \text{mm}$ 

Ports 1 Ethernet

1 Mini USB slave1 USB host1 proprietary host

PIN Pad Internal, 3DES encryption,

DUKPT key management

Communication EVDO (CDMA), HSPA (GSM),

Ethernet, WiFi (optional)

**Size**  $L \times W \times H = 180 \times 80 \times 69 \text{mm}$ 

Weight 500g

**Environment** Operating temperature: 0°C to 50°C

(32°F to 122°F); humidity (non-condense): 10% to 90%; storage temperature: -20°C to 60°C (-4°F to 140°F); humidity

(non-condense): 5% to 95%

Power Supply Input: 100-240V, 50-60Hz

Output: 8.5V/2.5A

Battery Li-ion 1850mAh

**Certifications** PCI PTS 4.x, PA-DSS 3.x, Paywave,

Paypass, EMV Level 1 & 2

Optional 5MP camera

1D barcode scanner 2D QR code scanner Micro SD card support

